

DETAIL	FG 33 A08 CRAWLER TRACKS
D. with building dump (mm)	1810x1060x1350
D. with drum lt 350 (mm)	1890x1060x1350
D. with dump discharge mt. 1,5 (mm)	1890x1060x1350
D. with farm dump (mm)	1890x1060x1350
Dimension dozer blade (mm)	770x221
D. with selfcharging shovel (mm)	2660x1060x1350
Machine weight (kg)	490
A.W. building dump (kg)	70
A.W. with drum lt 350 (kg)	100
A.W. dump discharge mt. 1,5 (kg)	225
A.W. farm dump (kg)	60
A.W. dozer blade (kg)	40
A.W. selfcharging shovel (kg)	60
Capacity building pump (kg)	800
Capacity drum (lt)	350
Mix capacity (lt)	300
Capacity farm dump (kg)	800
Max speed (km/h)	2,3/3,2
Gasoline engine	Honda GX 270 (Hp 9) Avv. strappo Optional Honda GX390 (Hp 13) Avv. Elettrico
Diesel engine	Yanmar L100 (Hp 10) Avv. Elettrico
Track dimension (mm)	200x37x72
Min. light from the ground (mm)	120
Rotation ray baricenter (mm)	910
Hydraulic engine	EPRM.L315
Hydraulic pump	PLP 10-4 3/4 UNIT
Pump capacity	3/4 unit x 4cc/rev (5,82 Lt a 1.500 giri)
Oil pressure (bar)	130
Allowed inclination % (incl.)	46% (25°)